



ENERG

енергия · ενεργεια



NIBE AMS10-12 + BA-SVM10-200/12 R



A++



A

Two icons showing sound power levels: a speaker icon with a house inside labeled **35 dB**, and a house icon with a speaker inside labeled **58 dB**.



Legend for power capacity with three colored squares: dark blue for **13 kW**, medium blue for **10 kW**, and light blue for **12 kW**.











ENERG


енергия · ενεργεια





NIBE


AMS10-12 + BA-SVM10-200/12 R













+ 

+ 

+ 


+ 

Supplier's name:	NIBE		
Model:	AMS10-12 + BA-SVM10-200/12 R		
Temperature application	35	55	°C
Declared load profile for water heating	XL		
Seasonal space heating energy efficiency class, average climate:	A++	A++	
Water heating energy efficiency class, average climate:	A		
Rated heat output, average climate:	11,5	10,0	kW
Annual energy consumption for space heating, average climate	5382	6136	kWh
Annual electricity consumption for water heating, average climate	1702		kWh
Seasonal space heating energy efficiency, average climate:	174	132	%
Water heating energy efficiency, average climate:	98		%
Sound power level LWA indoors	35		dB
Rated heat output, cold climate:	11,5	13,0	kW
Rated heat output, warm climate:	12,0	12,0	kW
Annual energy consumption for space heating, cold climate	7798	11197	kWh
Annual electricity consumption for water heating, cold climate	1904		kWh
Annual energy consumption for space heating, warm climate	2759	3419	kWh
Annual electricity consumption for water heating, warm climate	1551		kWh
Seasonal space heating energy efficiency, cold climate:	142	111	%
Water heating energy efficiency, cold climate:	88		%
Seasonal space heating energy efficiency, warm climate:	229	185	%
Water heating energy efficiency, warm climate:	108		%
Sound power level LWA outdoors	58		dB

Data for package fiche

Controller class	VI		
Controller contribution to efficiency	4,0		%
Seasonal space heating energy efficiency of package, average climate:	178	136	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A++	%
Seasonal space heating energy efficiency of package, cold climate:	146	115	%
Seasonal space heating energy efficiency of package, warm climate:	233	189	%

Model(s):				AMS10-12 + BA-SVM10-200/12 R								
Type of heat source/sink:				Air-to-water								
Low-temperature heat pump:				No								
Equipped with supplementary heater:				Yes								
Heat pump combination heater:				Yes								
Climate condition:				Average								
Temperature application:				Medium temperature (55 °C)								
Applied standards: EN14825, EN16147												
Rated heat output				Prated	10,0	kW		Seasonal space heating energy efficiency				
								η_s	132	%		
<i>Declared capacity for part load at outdoor temperature Tj</i>								<i>Declared coefficient of performance for part load at outdoor temperature Tj</i>				
Tj = -7 °C	Pdh	8,9	kW		Tj = -7 °C	COPd	1,99	-				
Tj = +2 °C	Pdh	5,5	kW		Tj = +2 °C	COPd	3,22	-				
Tj = +7 °C	Pdh	3,5	kW		Tj = +7 °C	COPd	4,61	-				
Tj = +12 °C	Pdh	5,0	kW		Tj = +12 °C	COPd	6,25	-				
Tj = biv	Pdh	9,2	kW		Tj = biv	COPd	1,90	-				
Tj = TOL	Pdh	8,1	kW		Tj = TOL	COPd	1,92	-				
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW		Tj = -15 °C (if TOL < -20 °C)	COPd		-				
Bivalent temperature				T _{biv}	-7,9	°C		Operation limit temperature				
Cycling interval capacity for heating				P _{cyh}		kW		Cycling interval efficiency				
Degradation co-efficient				Cdh	0,98	-		Heating water operating limit				
								WTOL	58	°C		
<i>Power consumption in modes other than active mode</i>								<i>Supplementary heater</i>				
Off mode	P _{OFF}	0,002	kW		Rated heat output				P _{sup}	1,9	kW	
Thermostat-off mode	P _{TO}	0,014	kW		Type of energy input				Electric			
Standby mode	P _{SB}	0,015	kW									
Crankcase heater mode	P _{CK}	0,035	kW									
<i>Other items</i>												
Capacity control				variable				Rated air flow rate, outdoors				
Sound power level, indoors/outdoors				L _{WA}	35/58	dB		Rated water flow rate, indoor heat exchanger				
Annual energy consumption				Q _{HE}	6136	kWh		Rated brine or water flow rate, outdoor heat exchanger				
											m ³ /h	
											m ³ /h	
											m ³ /h	
<i>For heat pump combination heater:</i>												
Declared load profile								Water heating energy efficiency				
								η_{wh}				
								98				
								%				
Daily electricity consumption				Q _{elec}	7,75	kWh		Daily fuel consumption				
Annual electricity consumption				AEC	1702	kWh		Annual fuel consumption				
								Q _{fuel}		kWh		
								AFC		GJ		
Approved by:												
Contact details				© NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden								